

7000-ME (5 PLY)

1 PLY LVL CORE, ANTI-WARPING, FOR INTENSIVE USE

- ① **STILES:** 7/8" (22 mm) wide hardwood, matched with faces. **Bonded to core**
- ② **TOP AND BOTTOM RAILS:** 7/8" (22 mm) in wood or SCL. **Bonded to core**
- ③ **CORE:** 1/8" (3 mm) thick veneer, longitudinally laminated by hot pressing with type 1 structural glue, as per ASTM D5456 93 (LVL). LVL is **FSC Certified** (UFF).
- ④ **FACES:** Wood veneer (choice of face veneers; 2 ply plywood), hardboard panel or plastic laminate glued to composite crossband

LOCK BLOCK: Integrated

GLUE: Type 1 PVA Cross link (UFF)

INTERIOR USE

REFERENCE SCLC 5/SCLC 7 (AWI/AWMAC)

WARRANTY: LIFETIME

OPTIONS


- | 20 minute fire rating, specify 7020 ME
- | Wood veneer glued to veneer plywood (3 ply plywood)
- | 3 5/16" (85 mm) LVL rails (hardware)
- | * To optimize M.R. 7.0, specify FSC wood veneer faces
- | *** To get I.E.Q. 4.4, specify UFF wood veneer faces

NOTE

| Dimensions are nominal before trimming.




Standards meet or exceed:
AWS section 9, October 1, 2009,
W.D.M.A. 1.S.1A 04 and
CSA 0132.2 90



LEED ELIGIBLE CREDITS	M.R.		I.E.Q.				
	4.1	4.2	5.1	5.2	6.0	7.0	4.4 (UFF)
			✓	✓		✓*	***

① STILES ME



② RAILS

